



Applications:

Remove any surface dirt or dust with a treated mop. Wash floor with a neutral detergent. Dilute with unheated tap water according to the dilution rates listed below.

Mop-on application: Apply with a clean mop daily to enhance the gloss and preserve the finish in traffic areas.

Auto-scrubbers: Fill scrubber reservoir. Regulate the flow of the solution at a low, steady rate. Apply just enough pressure on the

pad assembly to touch the surface of the floor. The rejuvenated area will be ready for traffic in minutes after cleaning.

Rinse the automatic scrubber tank thoroughly with water after use to prevent film build-up.

Dry burnishing: Routinely, apply with a clean mop. Allow the solution to dry for 30 minutes before dry burnishing with

UHS buffing pad.

Benefits:

- Extends the life of floor finish
- Increases slip resistance
- Built in detergents to clean
- Removes scuff and black marks
- Safe for all types of flooring
- Restores shine to eliminates frequent refinishing

Codes:

 Product Code: 52119

• UPC: 0 56069 53709 2

Specifications:

| Colour | White |
|------------|-----------------------------------|
| DIN | No |
| Odour | Acrylic |
| рН | 8.2 - 8.8 |
| Viscosity | Not determined |
| Solvent | No |
| Phosphates | No |
| WHMIS | Yes |
| ECOLOGO | Yes |
| Food Safe | No |
| Kosher | Yes |
| COF | 0.6 |
| Shelf Life | Up to 3 years after manufacturing |

Dilution Rates:

UL ECOLOGO (UL 2759) / Mop-On / Auto-Scrubber

1:20



Dry Burnishing

Available Format:

Packaging: Bottle:

5.8" x 5.8" x 12.3" (14.7 x 14.7 x 31 cm)

10 lbs (4.5 kg)

11.6" x 11.6" x 12.9" Box:

40 lbs (18 kg) 4 per case







