

# Attac<sup>®</sup> SC

### **High Efficiency Floor Stripper**

Highly concentrated low odor floor stripper formulated to meet Green  ${\rm Seal}^{\otimes}$  requirements.

#### Features & Benefits

- Powerful, fast-acting, low foam formula quickly bites through layers of finish as soon as it is applied
- Delivers fast, consistent removal of floor finish
- Not formulated with butyl or ammonia resulting in a minimal odor, suitable for facilities where odor is a concern
- Meets Green Seal  $^{\otimes}$  GS 40 standard based on effective performance and protective limits on VOCs

#### Applications

- Designed for floor finish removal on VCT, terrazzo, and concrete flooring
- Not intended for use on wood, linoleum, rubber, marble, painted surfaces, on surface colored and acid dyed concrete floors as this product may harm these surfaces
- Test for softening or color bleeding on asphalt floors before using







## Attac<sup>®</sup> SC

#### Use instructions

- Use appropriate personal protective equipment.
- Dilute product as follows: Dispense stripper solution from dispenser using cold water at 1:13 for heavy duty stripping (14 + coats) or 1:20 for light/medium duty stripping (4-13 coats) into appropriate container.
- Blockade areas to be stripped. Floors will be very slippery when stripper is applied. Exercise caution.
- Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water.
- Let stripper solution soak for 10-15 minutes. Mop agitate to loosen finish or sealer. Re-wet as necessary, do not allow stripper to dry on the floor. Longer soak times may be necessary in cases of extreme buildup.
- Hand or machine scrub thoroughly using appropriate stripper pads or stripping brush.
- Pick-up all of the solution with a clean mop, wet vac or automatic scrubber.
- Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry. Thoroughly rinse floor with clean water, using a mop and bucket.
- Let floor dry completely before applying a Diversey Green Seal<sup>®</sup>- certified finish or other recommended Diversey brand floor finish or sealer.

Technical data	Attac <sup>®</sup> SC		
Certifications	Green Seal®		
Color/Form	Clear Light Amber Orange, liquid		
pH	12.25		
Scent	Solvent		
Shelf Life	2 Years		

Product	Pack size	Dilution	Product code	
Attac® SC	1 x 5 L / 1.32 gal. RTD® Unit	1:13, 1:20	95580067*	I+I

\* Green Seal GS-40 Certified

#### Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.

\*This product meets Green Seal<sup>®</sup> Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

Green Seal® Certified mark is a registered certification mark owned by Green Seal, Inc.